





WINDOW CRIMP™

WITH SURE GRIP

Faster

- Single use pulling crimps
- Install faster than traditional pulling heads
- Compact
- Internal threads offer more surface area for crimping

Smarter

- Window allows for easy visual inspection of wire placement
- Works with aluminum or copper conductors

Safer

- Stronger and more secure
- Guaranteed when installed by an iTOOLco certified installer

iTOOLco's WINDOW CRIMP™ WITH SURE GRIP NOW AVAILABLE AT

Priority Wire & Cable

CERTIFIED INSTALLER





1. Strip the wire to allow full insertion into the head.



2. Insert the bare wire into the head past the window.



 Use the WCT 1000 tool, or similar 12 ton die crimping tool, to squeeze the crimp head in one or two positions depending on the iTOOLco specifications.

Priority Wire & Cable, Inc. (800)945-5542 www.prioritywire.com





Pulling Eyes

PWC Part Number	THHN/XHHW Conductor Size	Holding Value / lbs	Lanyard Lengths / inches	Number of Crimps
PG-6AWG	6	300	11, 15, 19, 23	One
PG-4AWG	4	350	11 ,15, 19, 23	One
PG-3AWG	3	500	11, 15, 19, 23	One
PG-2AWG	2	600	11, 15, 19, 23	One
PG-1AWG	1	1000	11, 15, 19, 23	One
PG-1/0AWG	1/0	1100	14, 21, 28, 35	Two
PG-2/0AWG	2/0	1100	14, 21, 28, 35	Two
PG-3/0AWG	3/0	1500	14, 21, 28, 35	Two
PG-4/0AWG	4/0	1700	14, 21, 28, 35	Two
PG-250MCM	250	2000	14, 21, 28, 35	Two
PG-300MCM	300	3000	14, 21, 28, 35	Two
PG-350MCM	350	4000	14, 21, 28, 35	Two
PG-400MCM	400	4500	14, 21, 28, 35	Two
PG-500MCM	500	5000	14, 21, 28, 35	Two
PG-600MCM	600	5500	14, 21, 28, 35	Two
PG-750MCM	750	5500	14, 21, 28, 35	Two
PG-1000MCM	1000	5500	14, 21, 28, 35	Two

^{*} All values are nominal and subject to correction

Application: Pulling Eyes are used to be crimped to the end of Aluminum or Copper THHN/XHHW to be pulled through conduit.