



RWS - Flexible Conduit Reduced Wall Steel

Part Number	Internal Diameter		External Diameter		Bending Radius (inch)	Weight lbs Per 100 ft.
	Min (inch)	Max (inch)	Min (inch)	Max (inch)		
RWS-3/8	0.375	0.393	0.560	0.610	2.00	19.5
RWS-1/2	0.625	0.645	0.860	0.920	3.00	27
RWS-3/4	0.891	0.835	1.045	1.105	4.00	35.1
RWS-1	1.000	1.040	1.300	1.380	5.00	52
RWS-1-1/4	1.250	1.300	1.550	1.630	6.25	62
RWS-1-1/2	1.500	1.575	1.850	1.950	7.50	88
RWS-2	2.000	2.080	2.350	2.450	10.00	114
RWS-2-1/2	2.500	-	2.860	3.060	12.50	184
RWS-3	3.000	-	3.360	3.560	15.00	202
RWS-3-1/2	3.500	-	3.860	4.060	17.50	156
RWS-4	4.000	-	4.360	4.560	20.00	210

All values are nominal and subject to correction.

Application: Flexible steel conduit can be used where UL listing is required. The 3/8" trade size also carries Canadian Standard Certification.

Construction: Premium hot dip galvanized zinc coated steel construction provides superior corrosion resistance. The smooth interior for easy wire pull through along with extra flexibility, allows simplified positioning and installation. For fixture whip and modular wiring assemblies, a special version lays straight and flat for a custom cut, and easy wire insertion.

Standards: Complies with UL-1 File Number E25633
NEC Article 350 and WW-C-566C
3/8 RWA is CSA Certified File Number 14901

1-800-945-5542