

Single Conductor 35KV, MV-105, 100% EPR/PVC Copper Tape Shield



APPLICATION:

35KV Shielded MV-105 cable is primarily used for power circuits in commercial, industrial, refinery and petro-chemical plants; utility power generation and substations. The cable can be installed in wet or dry applications and is for use in aerial, conduit, open tray, and underground duct installations. It can be used in direct burial if installed with a ground conductor in close proximity. The cable is approved for temperature up to 105°C and voltages up to 35000 volts.

CONDUCTORS:

- Class B annealed compact bare copper per ASTM

CONDUCTOR SHIELD:

- Extruded thermoset semi-conducting stress-control layer over conductor

INSULATION:

- High dielectric strength lead-free EPR insulation, contrasting in color to the black semi-conducting shield layers

INSULATION SHIELD:

- Extruded thermoset semi-conducting polymeric layer free stripping from insulation

METALLIC SHIELD:

- Helically applied 5 mil annealed copper tape over the insulation shield with an overlap of 25%

JACKET:

- Black low-friction, lead-free, flame-retardant, moisture and sunlight resistant polyvinyl chloride (PVC) jacket tightly applied over the copper tape

STANDARDS:

Meets or exceeds the following standards as applicable:

- UL 1072
- UL Listed as Type MV-105 for use in accordance with NEC
- AEIC CS8
- ICEA S-93-639/NEMA WC74
- ICEA S-97-682
- UL 1685 UL Flame Exposure Test
- IEEE 1202 Flame Test (70,000 BTU/hr)/CSA FT4
- EPA 40 CFR, Part 261 for leachable lead content per TCLP method
- OSHA Acceptable

Part Number	Conductor Size	Conductor Diameter	Insulation Thickness	Insulation Diameter	Jacket Thickness	Overall Diameter	Cable Weight	Ampacity					
								Conduit in Air*		Underground Duct**		Tray***	
								90°C	105°C	90°C	105°C	90°C	105°C
1/0-0135KVEPUCMV105	1/0	0.34	345	1.080	0.080	1.31	1090	195	215	200	215	195	220
4/0-0135KVEPUCMV105	4/0	0.48	345	1.210	0.080	1.45	1547	295	330	295	315	295	335
350-0135KVEPUCMV105	350	0.62	345	1.360	0.080	1.60	2108	395	440	390	415	410	455
500-0135KVEPMV105	500	0.74	345	1.480	0.080	1.72	2650	480	535	465	500	510	565
750-0135KVEPVCMV105	750	0.91	345	1.670	0.110	1.96	3733	585	655	565	610	655	730
1000-0135KVSEPVC	1000	1.06	345	1.820	0.110	2.10	4651	675	755	640	690	780	870

All values are nominal and subject to correction

* Ampacities are in accordance with Table 310.60(C)(73) of the NEC for triplexed or three single conductor copper cables in isolated conduit in air based on a conductor temperature of 90°C (194°F) or 105°C (221°F), temperature denoted in column header, and an ambient air temperature of 40°C (104°F).

** Ampacities are in accordance with Table 310.60(C)(77) of the NEC for triplexed or three single conductor copper cables in underground ducts (three conductors per duct), based on a conductor temperature of 90°C (194°F) or 105°C (221°F), temperature denoted in column header, and an ambient earth temperature of 20°C (68°F), electrical duct arrangement per Figure 310.60 Detail 1, 100% load factor, and earth thermal resistance (rho) of 90.

*** Ampacities are based on single conductor Type MV-105 sizes #1/0 AWG and larger in an uncovered tray in accordance with Section 392.80(B)(2) of the NEC at an ambient air temperature of 40°C (104°F); the ampacities are based on 75% of the values per Table 310.60(C)(69), operating temperature denoted in column header. For cable trays with unventilated covers for more than 6 feet, the ampacities shall not exceed 70% of the values per Table 310.60(C)(69).



1-800-945-5542
www.PriorityWire.com

