

Little Rock
800-945-5542


Virginia Beach
757-361-0207

Baton Rouge
888-754-5707

Las Vegas
702-696-0001

Houston
888-388-6280

Kentucky
859-727-6100



EFLT

Extra Flexible Liquid-Tight Conduit

Application: EFLT gives lasting wiring protection on machine tools, portable tools, presses, welders, pumps, blowers, grinders, conveyors, heating equipment, and automated lines for forging, plating, molding, blasting, rolling, diecasting, processing, extruding, etc.

Description: Durable, abrasion resistant PVC jacket will not wrinkle or shrink from cut ends. The galvanized mechanical steel core provides complete protection against liquid and moisture vapor. EFLT resists sunlight, heat, oil, and chemical degradation. The smooth flexible interior provides extra easy wire pull thru.

Catalog No.	Description	Internal Diameter		External Diameter		Bending Radius	Weight per per 100 ft.
		Min	Max	Min	Max		
P01A13	EFLT 3/8"	.484"	.504"	.690"	.710"	1 1/2"	17
P02A13	EFLT 1/2"	.622"	.642"	.820"	.840"	2"	20
P03A13	EFLT 3/4"	.820"	.840"	1.030"	1.050"	2 3/4"	32
P04A13	EFLT 1"	1.041"	1.066"	1.290"	1.315"	5"	50
P05A13	EFLT 1 1/4"	1.380"	1.410"	1.630"	1.660"	6"	68
P06A13	EFLT 1 1/2"	1.575"	1.600"	1.865"	1.900"	7"	87
P07A13	EFLT 2"	2.020"	2.045"	2.340"	2.375"	9"	119
P08A13	EFLT 2 1/2"	2.480"	2.505"	2.840"	2.875"	11"	140
P09A13	EFLT 3"	3.070"	3.100"	3.460"	3.500"	15 1/2"	230
P10A13	EFLT 3 1/2"	3.500"	3.540"	3.960"	4.000"	18"	290
P11A13	EFLT 4"	4.000"	4.040"	4.460"	4.500"	22"	350
P12A13	EFLT 5"	4.975"	5.035"	5.505"	5.565"	30 1/2"	568

1-800-945-5542

© Priority Wire & Cable, Inc. Little Rock, AR, 2003 PWC02/2003