

Little Rock **Virginia Beach**
800-945-5542 **757-361-0207**

Baton Rouge **Las Vegas**
888-754-5707 **702-696-0001**

Houston **Kentucky**
888-388-6280 **859-727-6100**



www.prioritywire.com

COMPOSITE/HOME CONTROL 2 QUADS + 1 CAT5E

Two Coaxial cables CATV RG 6/U • 18 AWG CCS central conductor • Gas injected foam polyethylene insulation - Quad-shield, 2 aluminum braid plus 2 foil layers • PVC jackets, one black and the other white.

One four-pair Cat 5E Cable • Solid copper conductors • Polyethylene insulation
 • Twisted & cabled pairs • PVC jackets, one white and the other blue

Outside Jacket • A flame retardant PVC jacket 0.035" thick protects all the elements.
 • Overall diameter of cable is 0.748"

Application: Residential cabling with structured design for voice, data, video & any other high speed application.

Specifications: SCTE, ANSI/EIA/TIA 568 A, ANSI/ICEA S83-596. ISO-9001: Quality assurance system. UL: Flame performance. ETL: UTP category. PACKAGING: Wooden reels with a standard length of 500 ft.

COAXIAL CABLE PROPERTIES

Catalog No.	Central conductor Resistance to c.d.	Insulation diameter Inches (mm)	Overall diameter Inches (mm)	Braid coverage Resistance to c.d.	Impedance :	Capacitance/ Propagation Speed	Attenuation	
							MHz	dB/100 m
P01C6	0.40" (18 AWG) 99.5: /km	0.180" (4.47)	0.295" (7.5)	1 st 60% 2 nd 40 % 35.6 : /km	75+/-3	55.7pF/m 81 %	55	5.3
							211	10.0
							300	11.6
							450	14.4
							550	16.1
							750	18.4
							1000	21.5

TWISTED PAIR PROPERTIES

Jacket thickness Inches (mm)	Overall diameter Inches (mm)	Conductor gauge Resistance to c.d.	Impedance Zo	Mutual capacitance pF/ ft (pF/m)	Properties in 100 m (328 ft)		
					Frequency MHz	Attenuation dB	PSNEXT dB
0.02" (0.52)	0.185" (4.7)	24AWG 90.5: /km	100 +/- 15 from 1 to 350 MHz	14 (45.9)	4	4.1	53
					10	6.5	47
					16	8.2	44
					31.25	11.7	39
					62.5	17.0	35
					100	22.0	32

* Values shown are nominal, subject to manufacturing tolerances

1-800-945-5542

© Priority Wire & Cable, Inc. Little Rock, AR, 2003 PWC08/2005