

**Little Rock** **Virginia Beach**  
800-945-5542 757-361-0207

**Baton Rouge** **Las Vegas**  
888-754-5707 702-696-0001

**Houston** **Kentucky**  
888-388-6280 859-727-6100



## UL 3173 Chemically Cross-linked Polyethylene (XLP) (125C) (600 VOLTS) (UL & CSA)

**Application:** • Can be used for appliances, coil leads, switchboard panels, transformers, motor lead and power operated dispensing units.

**Construction:** 20 AWG, 18 AWG and 16 AWG are also printed with "Switchboard Wire" for SIS applications. 14 AWG through 4 AWG are also printed with "SIS" for non VW-1 SIS applications.

- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors:

Black, Dark Green, Brown, Gray, Dark Blue, Light Blue, Light Green, Orange, Pink, Purple, White, Red, Yellow, Tan

Catalog No.	AWG. SIZE	STANDARD STRANDING	NOMINAL INSUL.	NOMINAL DIAMETER	APPROX. LBS./MFT	UL TYPE	C.S.A. TYPE
P01110	20	10/30 Tinned	.030	.100	7	3173	CL1251/AWM
P02110	18	16/30 Tinned	.030	.109	10	3173	CL1251/AWM
P03110	16	26/30 Tinned	.030	.124	13	3173	CL1251/AWM
P04110	14	41/30 Tinned	.030	.142	19	3173	CL1251/AWM
P05110	12	65/30 Tinned	.030	.158	27	3173	CL1251/AWM
P06110	10	105/30 Tinned	.030	.192	42	3173	CL1251/AWM
P07110	8	133/29 Tinned	.045	.260	75	3195	CL1251/AWM
P08110	6	133/27 Tinned	.060	.338	125	3196	CL1251/AWM
P09110	4	133/25 Tinned	.060	.391	180	3196	CL1251/AWM

1-800-945-5542