

Little Rock **Virginia Beach**
800-945-5542 **757-361-0207**

Baton Rouge **Las Vegas**
888-754-5707 **702-696-0001**

Houston **Kentucky**
888-388-6280 **859-727-6100**



FLAT FESTOON - PVC CABLE

Specification: •Polyvinylchloride (PVC) (105C to -40C) (600 volts) (UL VW-11 and CSA FT-1)
 (Black and yellow)

Catalog No.	AWG SIZE	No. of Conductors	Stranding	INSULATION IN.	OUTER DIAMETER IN.	MM	AMPACITY USEC*	Approx. WT. #/MFT.	KG/KM
PO1113	16	8	65/34	.030	.225 X 1.170	5.7 X 29.7	15	194	289
PO2113	16	12	65/34	.030	.225 X 1.700	5.7 X 43.2	15	292	434
PO3113	14	4	105/34	.030	.240 X 0.690	6.1 X 17.5	20	138	206
PO4113	14	8	105/34	.030	.240 X 1.290	6.1 X 32.8	18	254	377
PO5113	14	12	105/34	.030	.240 X 1.825	6.1 X 46.4	18	380	566
PO6113	12	4	65/30	.030	.260 X 0.800	6.6 X 20.3	25	180	267
PO7113	12	8	65/30	.030	.260 X 1.440	6.6 X 36.6	22	343	510
PO8113	10	4	105/30	.030	.290 X 0.890	7.4 X 22.6	32	239	356
PO9113	8	4	168/30	.045	.375 X 1.225	9.5 X 31.1	45	401	596
P10113	6	4	259/30	.060	.435 X 1.490	11.0 X 37.8	60	620	923
P11113	4	4	413/30	.060	.515 X 1.750	13.1 X 44.0	78	896	1333
P12113	2	4	665/30	.060	.575 X 1.975	14.6 X 50.2	104	1278	1901

COND #	BASE	STRIPE	COND #	BASE	STRIPE	COND #	BASE	STRIPE
1	Black	-	5	Yellow	-	9	Orange	Black
2	Red	-	6	Brown	-	10	Yellow	Black
3	Blue	-	7	Red	Black	11	Brown	Black
4	Orange	-	8	Blue	Black	12	Black	Red

1-800-945-5542