

GROUND RODS ACCESSORIES

Ground Rod Couplings: UL CSA • Connects two copper sectional ground rods • Tapered ends to reduce driving friction • Constructed of high strength, corrosion resistant bronze

Direct Burial Ground Rod Clamps: UL CSA • Connects grounding conductor to driven copper ground rod • Approved for direct burial in the earth and concrete • Contains a bronze hex headed bolt • Constructed of high strength, corrosive resistant bronze **Bronze Water Pipe Ground Clamps:** UL CSA • Connects grounding conductor to driven galvanized ground rod • Constructed of high strength, highly conductive bronze • Steel screws plated for corrosion resistance

Cast Bronze Plated Water Pipe Ground Clamps: • Connects grounding conductor to galvanized ground rod

• Die cast zinc body with brass colored plating • Assembled with zinc plated steel screws for corrosion resistance Ground Rod Driving Studs: UL • Connects to copper sectional ground rods with a coupling for driving to eliminate damage to

ground rod threads • Constructed for high strength, corrosive resistant steel with bronze plating.

| Catalog No. | Size | Wire Size | | Standard Packaging | Weight per |
|-------------|--------------------------|-----------|------------|--------------------|------------|
| | | max | min | | 100 Pcs |
| Ground R | od Coupling | gs | • • | · · · · · · | |
| P01R3 | 1/2" | | - | 10 | 16 lbs |
| P02R3 | 5/8" | | - | 10 | 25 lbs |
| P03R3 | 3/4" | | - | 10 | 38 lbs |
| P04R3 | 1" | | - | 10 | 65 lbs |
| Direct Bu | rial Ground | Rod Clan | nps | | |
| P05R3 | 1/2" | - | - | 100 | 9 lbs |
| P06R3 | 5/8" | - | - | 50 | 10 lbs |
| P07R3 | 3/4" | - | - | 50 | 11 lbs |
| P08R3 | 1" | - | - | 50 | 19 lbs |
| Bronze W | ater Pipe G | round Cla | amps | | |
| P09R3 | ¹ /2" to 1" | # | 10 Sol | 25 | 19 lbs |
| P10R3 | 1 ¹ /4" to 2" | # | 10 Sol | 10 | 43 lbs |
| Cast Bron | nze Plated \ | Nater Pip | e Ground C | lamps | |
| P11R3 | 1/2" to 1" | # | 10 Sol | 100 | 17 lbs |
| Ground R | od Driving | Studs | | | |
| P12R3 | 1/2" | - | | 10 | 12 lbs |
| P13R3 | 5 _{/8} " | - | | 10 | 23 lbs |
| P14R3 | 3/4" | - | | 10 | 35 lbs |
| P15R3 | 1" | - | | 10 | 49 lbs |







