

Little Rock **Virginia Beach**
800-945-5542 **757-361-0207**

Baton Rouge **Las Vegas**
888-754-5707 **702-696-0001**

Houston **Kentucky**
888-388-6280 **859-727-6100**



www.prioritywire.com

QUADRUPLIX SERVICE DROP ALUMINUM CONDUCTOR

Applications: Used to supply 3 phase power, usually from a pole-mounted transformer, to the user's service head where connection to the service entrance cable is made. To be used at voltages of 600 volts or less phase to phase and at conductor temperatures not to exceed 75°C for polyethylene insulated conductors or 90°C for cross linked polyethylene (XLP) insulated conductors.

Construction: Conductors are concentrically stranded, compressed 1350-H19 aluminum. Insulated with either polyethylene or XLP cross linked polyethylene. Neutral messengers are concentrically stranded 6201, AAC, or ACSR.

Specifications: Quadruplex service drop cable meets or exceeds the following ASTM specifications: B-230 Aluminum Wire, 1350-H19 for electrical purposes. B-231 Aluminum conductors, Concentric-Lay-Stranded. B-232 Aluminum Conductors, Concentric-Lay-Stranded, Coated Steel Reinforced (ACSR) B-399 Concentric-Lay-Stranded, 6201-T81 Aluminum. Service Drop cable meets or exceeds all applicable requirements of ICEA S-76-474.

Code Word	Phase Conductors			Bare Neutral Messenger			Weight Per 1000ft (lbs)		Ampacity (AMPS)	
	Size AWG	Strand	Insulation Thickness (mils)	Size AWG	Strand	Breaking Strength (lbs)	XLP	POLY	XLP	POLY
AAC NEUTRAL MESSENGER										
Clydesdale	4	Solid	45	4	7	881	208	201	100	80
Pinto	4	7/w	45	4	7	881	223	207	100	80
Mustang	2	7/w	45	2	7	1,350	333	312	135	105
Criollo	1/0	19/w	60	1/0	7	1,990	529	504	180	135
Percheron	2/0	19/w	60	2/0	7	2,510	649	620	205	55
Hanoverian	3/0	19/w	60	3/0	19	3,310	799	765	235	180
Oldenburg	4/0	19/w	60	4/0	19	4,020	986	946	270	205
Lippizaner	336.4	19/w	80	336.4	19	6,146	1,546	1,519	330	240
ACSR NEUTRAL MESSENGER										
Morochuca	6	Solid	45	6	6/1	1,190	152	147	75	60
Chola	6	7/w	45	6	6/1	1,190	162	151	75	60
Morgan	4	Solid	45	4	6/1	1,860	226	220	100	80
Hackney	4	7/w	45	4	6/1	1,860	241	226	100	80
Palamino	2	7/w	45	2	6/1	2,850	362	342	135	05
Costena	1/0	19/w	60	1/0	6/1	4,380	575	550	180	135
Grullo	2/0	19/w	60	2/0	6/1	5,310	707	678	205	155
Suffolk	3/0	19/w	60	3/0	6/1	6,620	872	838	235	180
Appaloosa	4/0	19/w	60	4/0	6/1	8,350	1,079	1,039	270	205
Bronco	336.4	19/w	80	336.4	18/1	8,580	1,613	1,568	330	240
Gelding	336.4	19/w	80	4/0	6/1	8,350	1,548	1,494	330	240
6021 ALLOY NEUTRAL MESSENGER										
Bay	6	Solid	45	6	7	1,110	145	140	75	60
French Coach	6	7/w	45	6	1	1,110	155	144	75	60
Gerrnan Coach	4	Solid	45	4	7	1,760	214	208	100	80
Arabian	4	7/w	45	4	7	1,760	229	214	100	80
Belgian	2	7/w	45	2	7	2,800	344	323	135	105
Shetland	1/0	19w	60	1/0	7	4,460	546	521	180	135
Thoroughbred	2/0	19/w	60	2/0	7	5,390	670	641	205	155
Trotter	3/0	19/w	60	3/0	7	6,790	825	791	235	180
Walking	4/0	19/w	60	4/0	7	8,560	1,019	979	270	205

Note: Designated sizes are ACSR 6/1 diameter and AAC with equivalent resistivity per ASTM B-399 for 6201. Conductor temperature of 90°C for XLP, 75°C for Poly; ambient temp. of 40°, emissivity 0.9; 2 ft/sec/wind in sun.

1-800-945-5542