

Galvanized Steel Guy Strand



APPLICATION:

Guy wire is used to add stability to a free-standing structure or tower.

STANDARDS:

- Manufactured and inspected per ASTM A475 and BS-183
- RUS Approved

PACKAGING:

- 250' and 500' Coils with 18" ID
- 2,500' and 5,000' Reels
- Bulk cut to length

Part Number*	CONSTRUCTION				MINIMUM BREAKING STRENGTH				COATING	
	Strand Diameter	Coated Diameter	No. of Strands	Approx. Weight	Utilities Grade	Siemens-Martin Grade	High Strength Grade	Extra High Strength Grade	Zinc Coating	Min. Coating Weight Class A
	inches	inches		lbs/kft	lbs	lbs	lbs	lbs		oz/sq.ft.
1/4-7STR	1/4	0.080	7	121	-	3,150	4,750	6,650	100%	0.60
5/16-7STR	5/16	0.104	7	205	-	5,350	8,000	11,200	100%	0.80
3/8-7STR	3/8	0.120	7	273	11,500	6,950	10,800	15,400	100%	0.85
7/16-7STR	7/16	0.145	7	399	18,000	9,350	14,500	20,800	100%	0.90
1/2-7STR	1/2	0.165	7	517	25,000	12,100	18,800	26,900	100%	0.90
9/16-7STR	9/16	0.188	7	671	-	15,700	24,500	35,000	100%	1.00

All values are nominal and subject to correction.

*Root part number is listed. Let us know at time of order entry which strength you need and we will complete the part number.