

PRIORITY-PLEX™ Cable 600/1000V with Ground Black, Red, White



APPLICATION:

Priority-Plex™ XHHW-2 Conductors are primarily used for power distribution where light weight and flexibility are desired. XHHW-2 600/1000 volt conductors may be used in wet or dry locations at conductor operating temperatures not exceeding 90°C. Suitable for installation in raceways, channels, conduits and ducts, for ambient temperatures down to -40°C, and for use in accordance with National Electrical Code.

CONDUCTORS:

- Compact stranded AA-8000 series aluminum alloy

INSULATION:

- Cross-linked polyethylene (XLPE), solid colored, UL listed for sunlight resistant, -40°C

COLOR CODE:

120/208/240V

- 3+1: Black, Red, White + Green Ground

Note: Additional color code options are available upon request

ASSEMBLY:

- Insulated phase conductors with slick jacket are plex'd with an insulated ground wire

SPECIFICATIONS:

- UL44/C22.2 No.38
- UL 1685
- UL 2556
- ASTM B800
- ASTM B801

Part Number	Conductor Size	No. of Conductors	Ground Wire Size	Insulation Thickness		Approx Conductor Diameter		Approx Plexed Cable Diameter		Approx Plexed Cable Weight	Cable Ampacity* @90°C
	AWG/kcmil		AWG/kcmil	inches	mm	inches	mm	inches	mm	lbs/kft	amps
THREE CONDUCTORS PLUS GROUND											
6-03PPLEX-BRW-6G**	6	3	6	0.045	1.15	0.26	6.6	0.64	16.3	162	55
4-03PPLEX-BRW-6G**	4	3	6	0.045	1.15	0.31	7.9	0.72	18.3	215	75
2-03PPLEX-BRW-6G	2	3	6	0.045	1.15	0.36	9.2	0.82	20.9	298	100
1-03PPLEX-BRW-4G	1	3	4	0.055	1.40	0.41	10.4	0.94	23.9	396	115
1/0-03PPLEX-BRW-4G	1/0	3	4	0.055	1.40	0.45	11.5	1.03	26.2	470	135
1/0-03PPLEX-BRW-2G**	1/0	3	2	0.055	1.40	0.45	11.5	1.03	26.2	488	135
2/0-03PPLEX-BRW-4G	2/0	3	4	0.055	1.40	0.49	12.5	1.13	28.8	560	150
3/0-03PPLEX-BRW-4G	3/0	3	4	0.055	1.40	0.54	13.7	1.18	30.0	670	175
4/0-03PPLEX-BRW-2G**	4/0	3	2	0.055	1.40	0.59	15.0	1.30	33.1	825	205

All values are nominal and subject to correction.

*Ampacities for aluminum conductors in raceway or cable based on an ambient temperature of 30°C per NEC Table 310.16 for 3 current carrying conductors

**Non-stock item available for order



1-800-945-5542
www.PriorityWire.com



PRIORITY-PLEX™ Cable 600/1000V with Ground Black, White, Red



Part Number	Conductor Size	No. of Conductors	Ground Wire Size	Insulation Thickness		Approx Conductor Diameter		Approx Plexed Cable Diameter		Approx Plexed Cable Weight	Cable Ampacity* @90°C
	AWG/kcmil		AWG/kcmil	inches	mm	inches	mm	inches	mm	lbs/kft	amps
THREE CONDUCTORS PLUS GROUND											
250-03PPLEX-BRW-2G	250	3	2	0.065	1.65	0.65	16.5	1.44	36.7	990	230
300-03PPLEX-BRW-2G**	300	3	2	0.065	1.65	0.70	17.8	1.54	39.2	1150	260
350-03PPLEX-BRW-2G**	350	3	2	0.065	1.65	0.75	19.1	1.63	41.5	1285	280
400-03PPLEX-BRW-1G**	400	3	1	0.065	1.65	0.79	20.1	1.72	43.8	1465	305
500-03PPLEX-BRW-1G	500	3	1	0.065	1.65	0.87	22.1	1.88	47.9	1770	350
500-03PPLEX-BRW-2/0G**	500	3	2/0	0.065	1.65	0.87	22.1	1.88	47.9	1819	350
600-03PPLEX-BRW-1G**	600	3	1	0.080	2.04	0.98	24.9	2.13	54.2	2140	385
700-03PPLEX-BRW-1/0G**	700	3	1/0	0.080	2.04	1.04	26.5	2.25	57.3	2480	425
750-03PPLEX-BRW-1/0G**	750	3	1/0	0.080	2.04	1.07	27.2	2.32	59.1	2630	435
900-03PPLEX-BRW-1/0G**	900	3	1/0	0.080	2.04	1.17	29.8	2.53	64.4	3095	480

All values are nominal and subject to correction.

*Ampacities for aluminum conductors in raceway or cable based on an ambient temperature of 30°C per NEC Table 310.16 for 3 current carrying conductors

**Non-stock item available for order



1-800-945-5542
www.PriorityWire.com



©2024 Priority Wire & Cable
01-2024