



RWA-Flexible Conduit REDUCED WALL ALUMINUM

Part Number	Internal Diameter		External Diameter		Bending Radius	Weight
	Min	Max	Min	Max		
	inches	inches	inches	inches		
RWA3/8	0.375	0.393	0.560	0.610	2.00	7
RWA1/2	0.625	0.645	0.860	0.920	3.00	10
RWA3/4	0.812	0.835	1.045	1.105	4.00	11
RWA1	1.000	1.040	1.300	1.380	5.00	20
RWA1-1/4	1.250	1.300	1.550	1.630	6.25	22
RWA1-1/2	1.500	1.575	1.850	1.950	7.50	44
RWA2	2.000	2.080	2.350	2.450	10.00	44
RWA2-1/2	2.500	-	2.860	3.060	12.50	60
RWA3	3.000	-	3.360	3.560	15.00	74
RWA3-1/2	3.500	-	3.860	4.060	17.50	106
RWA4	4.000	-	4.360	4.560	20.00	128

All values are nominal and subject to correction.

Application: Allows electrical contractors to run hundreds of feet of conduit without installing connectors between sections of conduit or the need for frequent braces to support the weight.

Construction: Light weight, primary, tempered aluminum alloy provides maximum strength and flexibility. Superior resistance to corrosion with a smooth interior for easy pull through. Built in flexibility provides easy installation.

Standards: UL-1 Listed
 NEC Article 348
 Federal Specification WW-C-566C
 NEMA 1

1-800-945-5542