

# 8AWG-2AWG SE00W Portable Power Cable

## 90°C 600V



### APPLICATION:

SE00W Portable Power Cable is for use with portable tools, equipment, appliances, small motors and associated machinery where flexibility and durability are required. This cable is also suitable for use outdoors and for immersion in water. For applications up to 600 volts and for temperatures of -50°C to +105°C. NOTE: SE00W is not well suited for harsh environments such as quarries, mines or gravel pits.

### CONDUCTORS:

- Class K stranded soft drawn bare copper conductor per ASTM B174

### INSULATION:

- Color coded premium grade Thermoplastic Elastomer (TPE)

### JACKET:

- Overall jacket of black 105°C Thermoplastic Elastomer (TPE), which is oil, moisture and abrasion resistant
- Black and Yellow jackets are available

### STANDARDS:

- OSHA accepted
- Sunlight Resistant

### COLOR CODE:

ICEA S-58-679, Method 1, Table 1

No. of Conductors	Color
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green

Part Number	Conductor Size	No. of Conductors	Conductor Stranding	Nominal Insulation Thickness		Nominal Overall Diameter		Weight	Ampacity** 30°C Ambient
	AWG		No./AWG	inches	mm	inches	mm	lbs/kft	
8-03SE00W	8	3	65/0.0159	0.050	1.27	0.701	17.81	311	40
8-04SE00W	8	4	65/0.0159	0.050	1.27	0.783	19.89	402	35
6-03SE00W	6	3	133/0.0142	0.050	1.27	0.818	20.78	452	55
6-04SE00W	6	4	133/0.0142	0.050	1.27	0.892	22.66	575	45
4-03SE00W	4	3	133/0.0179	0.050	1.27	0.913	23.19	625	70
4-04SE00W	4	4	133/0.0179	0.050	1.27	1.027	26.09	821	60
2-03SE00W	2	3	133/0.0223	0.050	1.27	1.158	29.41	985	95
2-04SE00W	2	4	133/0.0223	0.050	1.27	1.260	32.00	1241	80

All values are nominal and subject to correction

\*\* Values shown are for current carrying conductors per NEC table 400.5(A)(1). A grounding conductor, or one which carries only the unbalanced current from other conductors, is NOT counted in determining current carrying capacity.



1-800-945-5542  
www.PriorityWire.com



©2020 Priority Wire & Cable  
02-2020